

CMP-TB-PT150

FM Approval Class Number 4431.  
OSHA Compliant.


OPTIONS:

1. DOME STYLE

STANDARD DOME   
TRI-ARCH



STANDARD DOME



CMP-TB-PT TRI-ARCH  
OUTER DOME

2. DOME MATERIAL

OUTER DOME - POLYCARBONATE  
INNER DOME (OPTIONAL)

Acrylic   
Polycarbonate   
Impact Modified   
Prismatic (Impact Modified)

3. GLAZING TINTS

OUTER DOME

Clear   
White   
Bronze

INNER DOME

Clear   
White   
Bronze

4. FRAME FINISHES

STANDARD MILL FINISH

CMP-TB-PT150	Qty	Standard Sizes
_____	_____	48" X 48"
_____	_____	48" X 96"
_____	_____	60" X 72"
_____	_____	60" X 96"

FOR CUSTOM SIZES PROVIDE OUTSIDE DIMENSION OF FINISH CURB

_____	_____	X
_____	_____	X

ORDER FORM  
CURB MOUNT POLYCARBONATE TB - PT150

DATE: \_\_\_\_\_ ORDER #: \_\_\_\_\_  
PROJECT: \_\_\_\_\_ LOCATION: \_\_\_\_\_  
CUSTOMER: \_\_\_\_\_ APPROVED: \_\_\_\_\_



PRODUCT OF ORCA MANUFACTURING, INC

- 1 Flashing Clearance is = 1/4"
- 2 Alum. Extruded Sash TB w/o weep holes
- 3 Fastener
- 4 Alum. Extruded Retaining angle
- 5 Glazing tape spacer
- 6 Wet seal
- 7 Fastener
- 8 Outer Polycarbonate Dome
- 9 Inner Dome (Optional)
- 10 Condensation Gutter
- 11 Weather strip tape (By others)
- 12 Glazing Tape (Typ.)
- 13 Curb and Roof Material (By Others)
- 14 Installation fastener (By others)

ORCA MANUFACTURING, INC.  
P.O. Box 992  
Hurlock, MD 21643  
PHONE (800) 776-1539  
FAX (410) 943-8245  
www.starlightskylights.com

