

CMP-TB-PT

FM Approval Class Number 4431.
OSHA Compliant.


OPTIONS:

1. DOME STYLE

STANDARD DOME
TRI-ARCH



STANDARD DOME



CMP-TB-PT TRI-ARCH
OUTER DOME

2. DOME MATERIAL

OUTER DOME - POLYCARBONATE
INNER DOME (OPTIONAL)

Acrylic
Polycarbonate
Impact Modified
Prismatic (Impact Modified)

3. GLAZING TINTS

OUTER DOME

Clear
White
Bronze

INNER DOME

Clear
White
Bronze

4. FRAME FINISHES

STANDARD MILL FINISH

CMP-TB-PT	Qty	Standard Sizes
_____	_____	48" X 48"
_____	_____	48" X 96"
_____	_____	60" X 72"
_____	_____	60" X 96"

FOR CUSTOM SIZES PROVIDE OUTSIDE DIMENSION OF FINISH CURB

_____	_____	X
_____	_____	X

ORDER FORM
CURB MOUNT POLYCARBONATE TB - PT

DATE: _____ ORDER #: _____
PROJECT: _____ LOCATION: _____
CUSTOMER: _____ APPROVED: _____



- 1 Flashing Clearance is = 1/4"
- 2 Alum. Extruded Sash TB w/o weep holes
- 3 Fastener
- 4 Alum. Extruded Retaining angle
- 5 Glazing tape spacer
- 6 Wet seal
- 8 Outer Polycarbonate Dome
- 9 Inner Dome (Optional)
- 10 Condensation Gutter
- 11 Weather strip tape (By others)
- 12 Glazing Tape (Typ.)
- 13 Curb and Roof Material (By Others)
- 14 Installation fastener (By others)

ORCA MANUFACTURING, INC.
P.O. Box 992
Hurlock, MD 21643
PHONE (800) 776-1539
FAX (410) 943-8245
www.starlightskylights.com

